

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 58211736
PUBLICATION DATE : 09-12-83


APPLICATION DATE : 03-06-82
APPLICATION NUMBER : 57094096

APPLICANT : TOSHIBA CORP;

INVENTOR : SHOROKU TAKESHI;

INT.CL. : G02F 1/11 B28D 5/00 C30B 29/30
C30B 33/00 G02B 1/02

TITLE : MANUFACTURE OF LITHIUM NIOBATE
SINGLE CRYSTAL ELEMENT



ABSTRACT : PURPOSE: To prevent cracking and chipping by cutting a single crystal ingot into a rotation-Y cut wafer and dicing the wafer in the direction of the line of intersection between the cleaved surface and surface of the wafer.

CONSTITUTION: LiNbO_3 is obtained and 41.5° rotation-Y cutting is performed to obtain the wafer 2 which has a straight line A rotated from an Y axis to a Z axis by 41.5° in the Y-Z plane of a hexagonal unit cell as the normal of the wafer surface. The directions of the lines of intersection between cleaved surfaces (1-102) and (01-12) and the wafer surface as the principal surface of the wafer 2 are set to directions M and N having specific angle relation with an orientation flat surface 3. The wafer 3 is fixed on the basis of the orientation flat surface 3 and diced at specific intervals so that dicing lines are in the directions M and N, thus forming cut grooves 4 and 5. Then, the wafer 2 is divided into single-crystal elements 6. Corner angles θ_1 and θ_2 are 133.5° and 46.5° .

COPYRIGHT: (C)1983,JPO&Japio